



Oceanside Oak



■ Cadiz Oak EDCAD6O3MM



■ Barcelona Spruce EDBAR6S3MM



■ Granada Walnut EDGRA6W3MM



■ Tortosa Sisal EDTOR6S3MM



■ Madrid Maple EDMAD6M3MM



■ Valencia Teak EDVAL6T3MM



■ Caceres Acacia EDCAC6A3MM



■ Montecito Oak SMMON7O3MM



■ Redondo Oak SMRED7O3MM



■ Piedmont Oak SMPIE7O3MM



■ Riata Hickory SMRIA7H3MM



■ Oceanside Oak SMOCE7O3MM



■ Bridle Hickory SMBRI7H3MM



■ Terret Walnut SMTER7W3MM



■ Pelham Maple SMPEL7M3MM

## Features

- Length: 48"
- Width:
  - 6"
  - 7.25"
- Thickness: 3mm  
20mil wear layer
- Finish: Surface Guardian Pro UV Coating
- Edge Detail: Microbevel
- FloorScore® Certified: Registration # SCS-FS-03695
- Warranty: Lifetime Residential Finish & Lifetime Residential Structure  
20 year Commercial Structural & 10 year Commercial Finish
- Maintenance: Clean with TrueClean Floor Cleaner.  
For full care and maintenance instructions visit [HallmarkFloors.com/Floor-Care-Maintenance](http://HallmarkFloors.com/Floor-Care-Maintenance)

## Benefits

- Fashion: Natural Low Sheen  
Embossed Wood Texture  
Fashionable Widths & Longer Lengths
- Performance: Waterproof  
Anti Bacterial & Fungal Control  
100% Renewable with Hallmark's ABC Recoat System  
PureCore Ultra- 100% Pure Virgin Vinyl
- Clean Air: Formaldehyde Free & Ortho Phthalate Free  
Safer Indoor Environment for Children  
100% FloorScore Certified



Piedmont Oak

## Trim Options

- Multipurpose Reducer
- T-molding
- Flush Stair Nosing

## Installation



Glue Down

Double Glue with Eternity LVT underlayment system or equivalent.



## ASTM Testing

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Stain Resistance	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F2199
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected	EN 7171-1

## ISO 14001 Certified Environmental Management System



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3