



Sovereign Oak COSOV7O7MM-18



Marquis Maple COMAR7M7MM-18



Margrave Teak COMAR7T7MM-18



Monarch Hickory COMON7H7MM-18



Chevalier Pine COCHE7P7MM-18



Paladin Walnut COPAL7W7MM-18



Imperial Oak COIMP7O7MM-18



Viscount Walnut COVIS7W7MM-18



Esquire Maple COESQ7M7MM-18



Vidame Hickory COVID7H7MM-18



Archduke Oak COARC7O7MM-18



Viceroy Maple COVIC7M7MM-18



Duchess Hickory CODUC7H7MM-18



Regent Eucalyptus COREG7E7MM-18



Baroness Hickory COBAR7H7MM-18



Kaiser Oak COKAI7O7MM-18



Vidame Hickory

Benefits

- Finish:** Anti Bacterial & Fungal Control
Commercially Rated Wear Layer
100% Renewable with Warranty Intact
Lifetime Finish Warranty
- Structure:** Higher Stability & Density
100% Quality Virgin Vinyl
Purcore Rigid Plus - Lifetime Structure
Warranty
- Clean Air:** Formaldehyde Free
Ortho Phthalate Free
100% Floor Score Certified

Features

- Length:** 59"
- Width:** 7"
- Thickness:** 5.5mm
- Wear Layer:** 20mil (.5mm)
- Finish:** Surface Guardian Pro UV Protection
- Edge Detail:** Pressed Bevel
- Certified:** FloorScore®
- Usage:** Residential / Light Commercial
- Warranty:** Limited Lifetime Residential finish
Limited Lifetime Residential structural
10 year commercial finish
20 year commercial structural
Renewable recoat system with warranty intact
- Install:** Click

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass (PSI Equivalent > 5,500+ lbs.)	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected	EN 7171-1
Impact Insulation Class IIC	IXPE Attached Pad 62 IIC	ASTM E-492, E-989
Sound Transmission Class	IXPE Attached Pad 52 STC	ASTM E-4316-16
ISO 14001 Certified Environmental Management System		



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3

