



Delaney Fabric

PLANK [6" x 48"]



Broadway Duomo Stone
TS6BRODS



Rockefeller Duomo Stone
TS6ROCDs




Central Park Wood End Grain
TS6CENWE



St. Mark's Wood End Grain
TS6STMWE


TILE [18" x 36"]



Madison Stone Concrete
TS18MADSC



5th Avenue Stone Concrete
TS18FTHSC




Wall Street Lineal Concrete
TS18WALLC



Canal Lineal Concrete
TS18CANLC



Delaney Fabric
TS18DELFA



Grand Central Fabric
TS18GRAFA



St. Mark's Wood End Grain

TIMES SQUARE
PLANK 6" x 48"

| | |
|---------------|---|
| Length: | 48" |
| Width: | 6" |
| Thickness: | 3mm |
| Wear Layer: | 20mil (.5mm) |
| Finish: | Surface Guardian Pro UV Coating |
| Edge Detail: | Beveled |
| Certified: | FloorScore® |
| Usage: | Residential / Commercial |
| Warranty: | Lifetime residential finish Lifetime residential structural 10 year commercial finish 20 year commercial structural Renewable recoat system with warranty |
| Installation: | Glue Down |

TIMES SQUARE
TILE 18" x 36"

| | |
|---------------|---|
| Length: | 36" |
| Width: | 18" |
| Thickness: | 3mm |
| Wear Layer: | 20mil (.5mm) |
| Finish: | Surface Guardian Pro UV Coating |
| Edge Detail: | Square |
| Certified: | FloorScore® |
| Usage: | Residential / Commercial |
| Warranty: | Lifetime residential finish Lifetime residential structural 10 year commercial finish 20 year commercial structural Renewable recoat system with warranty |
| Installation: | Glue Down |

Central Park Wood End Grain



| | | |
|--|--|------------------|
| Flexibility | Pass | ASTM F137 |
| Thickness | Pass | ASTM F386 |
| Standard Resistance to Chemicals [5 min.] | Pass | ASTM F925 |
| Resistance to Chemicals [24 hr.] | Pass | ASTM F925 |
| Heat Stability by Color Change | Pass | ASTM F1514 |
| Light Stability by Color Change | Pass | ASTM F1515 |
| Dimensional Stability after exposure to heat | Pass | ASTM F219 |
| Fire Resistance | Class C - Pass | ASTM E648 |
| Coefficient of Friction | Pass | ASTM D02047-04 |
| Static Load | Pass | ASTM F97D-D7 |
| Stain Resistance | Pass | ASTM F925 |
| Short Term Indentation | Pass | ASTM F19 14-98 |
| Smoke Density | Pass | ASTM E662-09 |
| Wear Resistance | High | ASTM F510-93 |
| Formaldehyde Emission [air] | None Detected *E1 Rating | EN 7171-1 |
| Impact Insulation Class IIC | Eternity Underlayment IIC 71 Delta 21 | ASTM E492, E-989 |

ISO 14001 Certified Environmental Management System



Certified Floorscore: Independent 3rd Party IAQ verification system for low emitting flooring.
Approved as CHPS 01350 compliant and recognized in LEED EQ Credit: 4.3